



General Information

Rig Name	Vantage 260
Rig Type	Independent Legs, Jackup, Cantilever
Rig Design	Class 150-44C Jack-up
Year Built	Delivery 1979
Year Upgraded	Major upgrade 2008/2015
Builder	Marathon Letourneau
Class	ABS \times A-1 Self-Elev. MODU code 1979
Flag	Liberia

General Specifications

Hull Length	181'
Hull Breadth	180'
Hull Depth	16'
No. of Legs / Type	3 / Triangular
Leg Spacing	87' Transverse 100' Longitudinal
Total leg length	250
Useable leg length	200 ft below hull
Accommodation	107 POB
Helideck	CAP 437 Rated for: Sikorsky S-61N
Spud Can Diameter	36'

Operational Capabilities

Water depth Max	150'
Water depth Min	12'
Transit Draft	11.3
Drilling Depth	20,000'
Cantilever	Aft reach 40' with 5' pin on extension x port/stb 10'
Variable Deck Load	4000 kips (Drilling) 62500 kips (Survival) 3240 kips (Transit)
Max Setback	800 kips

Dubai - UAE

Office 1801/1809/1910, Damac Executive Heights
Barsha Heights (Al Thanyah 1)
Dubai, United Arab Emirates
Tel: +971 4 449 3400 • Fax: +971 4 449 3401

Singapore

72 Anson Road
#07-01, Anson House
Singapore 079911
Tel: +65 6768 6000 • Fax: +65 6768 6001

Email: Marketing@Vantagedrilling.com

Environmental

Max Wave Height	40' (Operating)
Max Wave Height	43' (Survival)
Max Wind Speed	70 kts (Operating)
Max Wind Speed	100 kts (Survival)

Storage Capacities

Diesel	1,339 bbls
Drill Water	6,125 bbls
Potable Water	773 bbls
Bulk Barrite/Bentonite	3100 ft ³
Bulk Cement	3,100 ft ³
Active Mud	2086 bbls
Sack Store	3,000 sacks

Mud System

Working Pressure	5,000 psi
Mud Pumps	3 x Gardner Denver PZ-11 1600 HP
Shakers	3 x NOV Brandt King Cobra 1 x NOV Brandt King Cobra 16/2 Mud conditioner
Mud Manifold	1 x 4" ID , 5,000 psi WP

Cement System

Working Pressure	10,000 psi
Cement Unit	SLB Free Placement

Drilling Package

Derrick	Dreco 160' x 30' base X 14' top
Capacity	1,000,000 lbs Static hook load capacity
Racking Capacity	20,000 ft of " drill pipe range 20,000 ft of 3-1/2" drill pipe 450 ft og 8 inch Drillcollars 270 ft of 9 inch Drill Collars
Drawworks	National Type 1320-UE driven by two (2) GE-752 DC with a Baylor brake.
Rotary Table	NOV 37-1/2 in
Topdrive	NOV TDS-4S

For additional information please contact our Marketing offices:

Revision Date: April 2017

These specifications are intended for general reference purpose only and shall not be contractually binding. Contractor reserves the right to change these specifications at any time without prior notice. All equipment shall be operated and maintained in line with Vantage guidelines and within the limits of OEM specifications.

Handling Systems

Deck Cranes	3x Letourneau PCM-120-AS full revolving electric deck cranes with 100' boom length. Maximum capacity 50 tons at 25'.
BOP Handling Conductor Tensioner	2 x JD Neuhaus/EH50, 50 ton. 2 x 50 ton Top Tensioner

Well Control Equipment

Ram Preventers	13-5/8" 1x Cameron Type "U", 10,000 psi WP double ram preventer, H2S trim. 13-5/8" 1x Cameron Type "U", 10,000 psi WP single ram preventer, H2S trim.
Annular Preventer	13-5/8" 1x Shaffer annular preventer, 5,000# WP, H2S trim.
Diverter	1 x Shaffer spherical 21-1/4 inch 2000 psi with 12" flow line and 2 x 12" overboard lines
BOP Control System	CAD Control Systems BOP / Diverter control unit T series, , 3000 psi WP including local control, driller's control and tool pusher's control stations
Accumulator C & K Manifold	420 gals accumulators, 3000 psi 1 x 3 1/16" 10K HP side / 3 1/8", 5K, LP side, 1 x power chokes, 1 x manual chokes 1 x Remote Choke Console

Power Generation

Main Engines	4x Caterpillar D-3516A 1200 RPM / 1814 hp engines with Kato 600 Volt / 1500 KW Generators
Main Generators	Kato 600 Volt / 1500 KW Generators
SCRs	5x Ross Hill 1600 SCRs
Emergency Engines	1x Emergency Generator rated at 250 KW with 379 CAT 400 KW engine
Emergency Generators	1 x KATO 400 Generator, 1200 KW,

Life Saving Systems

Lifeboats	2 x 107 man capacity Belhai BH davit launched lifeboats (200% of POB)
Fast Rescue Craft	One dedicated rescue craft

Drill Pipes & Fishing Equipment

Drill Pipes	Various, details available on request
Fishing Equipment	Various, suitable to fish for Contractor's drill pipes